A+ WOOD STOVE VOGA (W+)

STANDARD SCOPE OF DELIVERY:

- Door for wood storage
- Profiled firebox lining
- Air flow handle

connection separately.

 Possibility for external combustion air connection comes as standard
Please order the connecting piece for external air

^{air} Optional

AVAILABLE

DESIGN: (1) Steel black

Can be extended by up to 3 additional segments (E-Blok or D-Blok). Height: 170 mm per E-Blok.

(1)



Illustration shows E-Blok with heat accumulation stone. D-Blok same illustration without heat accumulation stone.




24h


1<u>3</u>1

40cm









| Available design | | Order no. | EAN-Code |
|--|----------------|---------------|---------------|
| Voga (W+) , steel black | | 5698 11 | 4250340910941 |
| Optional accessories | | Order no. | EAN-Code |
| E-Blok (extension segment with heat accumulation stone W+) | | 9215 89 | 4250340911269 |
| D-Blok (extension segment) | | 9216 17 | 4029808596887 |
| Connecting piece for combustion air supply | | 9200 69 | 4029807779991 |
| | | | |
| Energy efficiency class | | A+ | |
| Connection possibility | | top / rear | |
| Operation with external air supply | | rear / bottom | |
| Nominal heat output | kW | kW 7,0 | |
| Weight (incl. packaging) | ca. kg | 21 | 10 |
| Weight E-Blok | ca. kg | 64 | |
| Room heating capability | m ³ | 131 | |
| Length of logs | cm | cm 40 | |
| Exhaust gas mass flow g/s | | 6,6 | |
| Exhaust gas temperature ° C | | 316 | |
| Required discharge pressure mbar | | 0,12 | |

